

Altair® Louvre Windows

POCKET GUIDE





breezway®

Altair® Louvre Window Standard Heights


Altair® Louvre Window Standard Heights						
	Altair® Louvre Galleries Component System (with weatherstrip ¹)			Altair® Powerlouvre™ Galleries Component System (with weatherstrip ²)		
Height	102mm	152mm	-	102mm	152mm	-
No. of Blades			IGLU™ System			IGLU™ System
2	-	330	335	-	360	365
3	320	470	475	350	500	505
4	410	610	615	440	640	645
5	500	750	755	530	780	785
6	590	890	895	620	920	925
7	680	1030	1035	710	1060	1065
8	770	1170	1175	800	1200	1205
9	860	1310	1315	890	1340	1345
10	950	1450	1455	980	1480	1485
11	1040	1590	1595	1070	1620	1625
12	1130	1730	1735	1160	1760	1765
13	1220	1870	1875	1250	1900	1905
14	1310	2010	2015	1340	2040	2045
15	1400	2150	2155	1430	2180	2185
16	1490	2290	2295	1520	2320	2325
17	1580	2430	2435	1610	2460	2465
18	1670	2570	2575	1700	2600	2605
19	1760	2710	2715	-	-	-
20	1850	2850	2855	-	-	-
21	1940	2990	2995	-	-	-
22	2030	-	-	-	-	-
23	2120	-	-	-	-	-
24	2210	-	-	-	-	-
25	2300	-	-	-	-	-
26	2390	-	-	-	-	-
27	2480	-	-	-	-	-
28	2570	-	-	-	-	-
29	2660	-	-	-	-	-
30	2750	-	-	-	-	-
31	2840	-	-	-	-	-
32	2930	-	-	-	-	-
33	3020	-	-	-	-	-

1. To calculate the gallery height only, deduct 10mm.
2. To calculate the gallery height only, deduct 40mm.

BLADE OPTIONS



CONTROL OPTIONS



COLOUR OPTIONS

Extensive range of colours and finishes available with colour matched clips and handles.



AWARD WINNING FEATURED OPTIONS

Powerlouvre™ System

Automated by the Apptivate™ Advance Control Unit or in response to temperature or timer events via App or BMS.



IGLU™ System

Double glazed louvre offering excellent ventilation and improved thermal insulation.

Stronghold™ System

Fall prevention compliant by mechanically retaining blades to provide extra strength and safety.



FOR MORE INFORMATION

breezway.co.nz or call 0800 777 759